



ACCELERATE SPEED AFFORDABLY

# MOTOROLA PTP 200 SERIES SOLUTIONS

Our Point-to-Point (PTP) 200 Series Wireless Ethernet Solutions are designed to give you high-throughput, reliable broadband communications on a tight budget. With a PTP 200 Series solution, enterprises, government organizations and service providers with limited resources can establish and extend backhaul communications affordably.

## MEETING YOUR NEEDS

Within our PTP 200 Series family of products<sup>1</sup>, you can choose among three line-of-sight (LOS) and near-line-of-sight (nLOS) solutions – two new systems, plus our existing PTP 49200 system which operates in the 4.9 GHz public safety band at data rates up to 21 Mbps. The new PTP 58230 operates in the 5.8 GHz license-exempt band at data rates up to 50 Mbps, while the new PTP

5X250 system is a dual-band<sup>2</sup> radio operating in the 5.4 and 5.8 GHz license-exempt bands at data rates up to 220 Mbps. Having an array of value-priced, high-quality communication options makes it easy to obtain the right combination of features to meet your specific application, infrastructure and environmental requirements.

## WIRELESS NETWORK SOLUTIONS

PTP 200 Series solutions are included in our Wireless Network Solutions portfolio. This portfolio delivers seamless connectivity that puts real-time information in the hands of users, giving you the agility you need to grow your business or better protect and serve the public. Our unrivaled wireless network solutions include indoor WLAN, outdoor wireless mesh, point-to-multipoint and point-to-point networks as well as voice over WLAN solutions. Combined with powerful software for wireless network design, security, management and troubleshooting, our solutions deliver trusted networking and anywhere access to organizations across the globe.

<sup>1</sup> Because PTP 200 Series products are based on three different platforms, upgrades between platforms are not available.

<sup>2</sup> In the first release, only the 5.8 GHz band will be available in the U.S. and Canada.

**PRODUCT SPEC SHEET**  
PTP 200 SERIES

**RADIO TECHNOLOGY**

RF bands <sup>3</sup>	Defined-Use Licensed Band: 49200: 4.940 – 4.990 GHz License-Exempt Bands: 58230: 5.725 GHz – 5.875 GHz 5X250: 5.470 GHz – 5.725 GHz 5.725 GHz – 5.850 GHz
Channel size	In all cases, channel sizes depend on region code. 49200: 10 MHz 58230: Configurable to 10 or 20 MHz 5X250: Configurable to 20 or 40 MHz
Channel selection	49200, 58230: Manual selection 5X250: Automatic selection on start-up, with manual override
Transmit power <sup>4</sup>	49200: Auto transmit power control by Master up to 18 dBm 58230: -30 to +19 dBm to EIRP limit by region (1 dBm interval) 5X250: Up to 22 dBm; varies with modulation mode and settings
System gain <sup>4</sup>	49200: Integrated – Up to 141 dB using Integrated antenna 58230: Integrated – Up to 125 dB using Integrated antenna LENS – Up to 137 dB using passive LENS Reflector – Up to 155 dB using passive reflector 5X250: Integrated – Up to 158 dB using 23 dBi Integrated antenna  System gain will vary with modulation mode and antenna type.
Receiver sensitivity	49200: Up to -89 dBm (with FEC) 58230: Up to -86 dBm (with FEC) 5X250: Adaptive, varying between -93 dBm and -71 dBm
Modulation	49200: Adaptive between QPSK, 16 QAM and 64 QAM 58230: Adaptive between QPSK, 16 QAM and 64 QAM 5X250: Dynamic; adapting between BPSK and 64 QAM with single and dual payload
Error correction	49200: ARQ, FEC (3/4 Reed-Solomon block coding) 58230: ARQ, FEC (3/4 Reed-Solomon block coding) 5X250: ARQ, FEC (based on IEEE 802.11n)
Duplex scheme	49200: Time Division Duplex (TDD) 58230: Time Division Duplex (TDD) 5X250: Time Division Duplex (TDD)
Antenna	In all cases, check local regulations prior to antenna purchase. 49200: Varies with antenna type; can operate with a selection of separately-purchased antennas, 50 ohm N-type 58230: Integrated – 10 dBi (55° antenna), can be enhanced with passive LENS or reflector dish

Antenna (continued)	5X250: Integrated flat plate 23 dBi / 7° Connectorized: Can operate with a selection of separately-purchased single and dual polar antennas through 2 x N-type female connectors
Maximum Range	49200: Integrated – Up to 15 mi (24 km) 58230: Integrated – Up to 4.5 mi (7.2 km) LENS – Up to 18 mi (29 km), Reflector – Up to 80 mi (128.7 km) 5X250: 20 MHz Channel – Up to 34 mi (54 km) 40 MHz Channel – Up to 17 mi (27 km)  Models vary with modulation mode and antenna type and size.
Security and encryption	49200: DES, FIPS 197 128-bit AES Encryption 58230: DES, FIPS 197 128-bit AES Encryption 5X250: Proprietary encryption

**ETHERNET BRIDGING**

Protocol	49200: Proprietary OFDM 58230: Proprietary OFDM 5X250: Proprietary, based on IEEE 802.11n
User data throughput	49200: Up to 21 Mbps (aggregate) 58230: 10 MHz Channel – Up to 24 Mbps 20 MHz Channel – Up to 50 Mbps 5X250: Up to 220 Mbps at the Ethernet (aggregate): 20 MHz Channel – Up to 110 Mbps 40 MHz Channel – Up to 220 Mbps
Latency (typical)	49200: 5 to 7 ms round trip 58230: 5 to 7 ms round trip 5X250: 4 ms round trip
QoS	49200: DiffServ QoS 58230: DiffServ QoS
Ethernet Interface	49200: 10/100 Base T (RJ-45) 58230: 10/100 Base T (RJ-45) 5X250: 1000 Base T (RJ-45), auto MDI/MDIX
VLAN	49200: 802.1Q with 802.1p priority 58230: 802.1ad (DVLAN Q-in-Q), 802.1Q with 802.1p priority, dynamic port VID

**MANAGEMENT & INSTALLATION**

LED indicators	49200: Power, GPS, Sync, Session, Link and Activity indicators 58230: Power, GPS, Sync, Session, Link and Activity indicators 5X250: Power status LED on Power Supply Unit (PSU)
System management	49200: HTTP, Telnet, FTP, SNMPv2c; compatible with Prizm 3.2 or later and CNUT 3.1 or later 58230: HTTP, Telnet, FTP, SNMPv2c; Wireless Manager, version 3.0 or higher 5X250: Web access via browser using proprietary PTP MIB
Installation	49200: Audio and LED indicators for link optimization 58230: Audio and LED indicators for link optimization 5X250: Built-in audio and graphical assistance for link optimization

<sup>3</sup> Regulatory conditions for RF bands should be confirmed prior to system purchase. Certain bands may not be available in all geographic regions.

<sup>4</sup> Gain, maximum transmit power and effective radiated power may vary based on regulatory domain.

**PRODUCT SPEC SHEET**  
PTP 200 SERIES

Connection	49200: Distance between outdoor unit and primary network connection: up to 330 ft. (100 meters)
	58230: Distance between outdoor unit and primary network connection: up to 330 ft. (100 meters)
	5X250: Distance between outdoor unit and primary network connection: up to 330 ft. (100 meters)

**PHYSICAL**

Dimensions	49200: H-13.25" (33.6 cm), W-8.25" (21 cm), D-4.38" (11.1 cm)
	58230: H-11.75" (29.9 cm), W-3.4" (8.6 cm), D-3.4" (8.6 cm)
	5X250: Integrated ODU: W-14.5" (370 mm), H-14.5" (370 mm), D-3.75" (95 mm) Connectorized ODU: W-12.2" (309 mm), H-12.2" (309 mm), D-4.1" (105 mm) PoE Power Supply: W-6.5" (165 mm), H-2.0" (50 mm), D-3.5" (88 mm)
Weight	49200: 2.8 lbs (1.3 kg)
	58230: 1 lb (0.6 kg)
	5X250: Integrated ODU: 12.1 lbs (5.5 kg) including bracket Connectorized ODU: 9.1 lbs (4.3 kg) including bracket PoE power supply: 0.83 lbs (378 g)
Operating temperature	49200: -40° to +131° F (-40° to +55° C)
	58230: -40° to +131° F (-40° to +55° C)
	5X250: -40° to +140° F (-40° to +60° C), including solar radiation
Wind speed survival	49200: 118 mph (190 kph)
	58230: 118 mph (190 kph)
	5X250: 150 mph (240 kph)

Power supply	49200: PoE power supply unit
	58230: PoE power supply unit
	5X250: PoE power supply unit
Power source	49200: 100-240 VAC, 50-60 Hz
	58230: 100-240 VAC, 50-60 Hz
	5X250: 100–240 VAC, 50–60 Hz
Power consumption	49200: 22 W max at 56 VDC
	58230: 9 W max at 30 VDC
	5X250: 35 W max

**ENVIRONMENTAL & REGULATORY**

Protection and safety	49200: UL60950; IEC60950; EN60950; CSA-C22.2 No. 60950; CB Approval for Global
	58230: UL60950; IEC60950; EN60950; CSA-C22.2 No. 60950; CB Approval for Global
	5X250: UL60950-1; CSA-C22.2 No. 60950-1 IEC60950-1:2005; EN60950-1:2006 + A11:2009 CB Approval for Global
Radio	49200: FCC – ABZ89FT7631, IC – 109W-4940
	58230: FCC – TBD, IC – 109W-5784, CE – EN302 502
	5X250: 5.4 GHz: EN301 893 5.8 GHz: FCC CFR 47, Part 15, sub-part C, 15.247; IC RSS210, Annex 8; EN 302 502
EMC	FCC CFR 47, 15.209 & 207, Class B; IC RSS210 Annex 8.5 & RSS Gen Para 7.2.2, Class B; EN301 489-1 & EN301 489-4, Class B

Note:  
The PTP 5X250 device has not been authorized in the 5.4 GHz band as required by the rules of the Federal Communications Commission and Industry Canada. This device is not, and may not be, offered for sale or lease, or sold or leased, as a dual-band device in the U.S. and Canada until authorization is obtained.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners.  
© 2011 Motorola Solutions, Inc. All rights reserved.

G3-23-128 WNS PTP 200 Series SS 020811

