


MOTOROLA WIRELESS BROADBAND

Point-to-Multipoint 58430 Access Point and Subscriber Module



The Motorola Wireless Broadband Point-to-Multipoint (PMP) 58430 Access Point and Subscriber Module is the ideal solution for developing, enhancing and extending advanced broadband networks with more than 45 Mbps of total aggregate throughput for data transfer, voice and video applications. The PMP 58430 Access Point and Subscriber Module provide wireless Line of Sight (LOS) and near Line of Sight (nLOS) broadband connectivity in the 5.8 GHz spectrum.

Motorola Wireless Broadband products combine field-proven toughness with exceptional performance, security, ease-of-use and cost effectiveness. PMP 58430 Series Access Point and Subscriber Modules are available with total throughputs up to 40 Mbps for data, video and voice applications. PMP 58430 Subscriber Modules can be purchased with throughputs of 4, 10, 20 or 40 Mbps and throughput can be enhanced to existing modules via a fixed software license.

The PMP 58430 Access Point can be co-located on the same tower location with other Motorola PMP Access Point solutions. The user guide provides details on co-location planning and network design considerations.

FEATURE	INTEGRATED AP SPECIFICATION	SM SPECIFICATION
	CAP 58430	CSM 58430
MODEL NUMBER	5780AP, 5780APC, 5780APUS	5790SM4, 5790SM10, 5790SM20, 5790SM40
PART NUMBER	5780CAA	5790AA, 5794AA
FREQUENCY RANGE	5725-5875 MHz	
CHANNEL WIDTH	10 MHz or 20 MHz	
CHANNEL SPACING	Configurable on 5 MHz increments	
# OF SELECTABLE, ADJACENT CHANNELS	Up to 15 (for 10MHz channel width) Up to 7 (for 20MHz channel width)	
ANTENNA GAIN	17 dBi (w/ included sector antenna)	10 dBi
TRANSMIT POWER (NOTE 1)	-30 to +21 dBm (to EIRP limit by region) (1dBm interval)	Auto transmit power control up to EIRP limit
MAX TRANSMIT POWER	1X: 21dBm, 2X: 21 dBm, 3X: 19 dBm	1X: 19 dBm, 2X: 19 dBm, 3X: 18 dBm
EIRP	36 dBm FCC 36 dBm ETSI (20 MHz) 33 dBm ETSI (10 MHz)	Unregulated by FCC 36 dBm ETSI (20 MHz) 33 dBm ETSI (10 MHz)
ANTENNA BEAM WIDTH	4 sector application (actual 3 dB antenna pattern: 60° horizontal 5° elevation; null fill)	55° horizontal 55° elevation 3 dB antenna pattern
ANTENNA CONNECTION	50 ohm N-type	N/A

**POINT-TO-MULTIPOINT 58430 ACCESS POINT
AND SUBSCRIBER MODULE**

FEATURE	INTEGRATED AP SPECIFICATION		SM SPECIFICATION
	CAP 58430		CSM 58430
MODULATION LEVELS (ADAPTIVE)	1X=QPSK, 2X=16QAM, 3X=64QAM		
FORWARD ERROR CORRECTION	¾ Reed-Solomon block coding		
PHYSICAL LAYER	OFDM 256FFT		
MAC (MEDIA ACCESS CONTROL) LAYER	Motorola Proprietary		
CYCLIC PREFIX	1/4 or 1/8 fixed		
PPS	6,800		4,800
GPS SYNCHRONIZATION		Yes	
# OF SUBSCRIBERS PER SECTOR	Up to 200		N/A
ARQ		Yes	
QUALITY OF SERVICE		DiffServ QoS	
MAXIMUM DEPLOYMENT RANGE (W/ REFLECTOR DISH ON SM, LOS)	1X: 30 mi. (48 km), 2X: 12.5 mi. (20 km), 3X: 4.5 mi. (7.3 km)		
MAXIMUM AGGREGATE (UP+DOWN) THROUGHPUT PER SECTOR (@10MHZ BANDWIDTH)	1X: 7.5 Mbps, 2X: 15 Mbps, 3X: 22.5 Mbps		
MAXIMUM AGGREGATE (UP+DOWN) THROUGHPUT PER SECTOR (@20MHZ BANDWIDTH)	1X: 16.5 Mbps, 2X: 33 Mbps, 3X: >45 Mbps		
LATENCY	5-7 ms round trip		
ENCRYPTION	DES, FIPS 197 Certified AES Option		
NOMINAL RECEIVE SENSITIVITY (W/ FEC) @ 10MHZ CHANNEL	1X: -89 dBm, 2X: -80 dBm, 3X: -70 dBm		
NOMINAL RECEIVE SENSITIVITY (W/ FEC) @ 20MHZ CHANNEL	1X: -86 dBm, 2X: -77 dBm, 3X: -67 dBm		
ETHERNET INTERFACE	10/100BaseT, half/full duplex, rate auto negotiated (802.3 compliant)		
PROTOCOLS USED	IPv4, UDP, TCP, IP, ICMP, Telnet, SNMP, HTTP, FTP		
NETWORK MANAGEMENT	HTTP, Telnet, FTP, SNMPv2c Prizm 3.2 and One Point Wireless Manager 2.2		
VLAN	802.1Q with 802.1p priority		
CE (NOTE 2)	EN302 502 v1.2.1		
FCC ID	ABZ89FT7634		ABZ89FT7635
INDUSTRY CANADA CERT	109W-5780		109W-5790
TEMPERATURE	-40°C to +55°C (-40°F to +131°F) 0% – 95% relative humidity, non-condensing		
WIND SURVIVAL	190 km/hour (118 mi/hour)		190 km/hour (118 mi/hour)
WIND LOADING	90 lbs.		45 lbs.
DIMENSIONS (H X W X D)	73 x 21 x 28 cm (28.75" x 8.25" x 11")		30 x 9 x 9 cm (11.75" x 3.4" x 3.4")
WEIGHT	6.1 kg (13.5 lbs.) (w/ antenna) 2.8 kg (6.1 lbs.) (w/o antenna)		0.45kg (1 lb.)
MAX POWER CONSUMPTION	19W		10W
INPUT VOLTAGE	24 to 59 V		24 to 30 V
COLLOCATION WITH PMP 52100		Yes	
COLLOCATION WITH PMP 54100	Yes, 10MHz guard band separation or 5MHz with 3 ft vertical required; synchronization required		
COLLOCATION WITH PMP 58100	Yes, 10MHz guard band required or 5MHz with 3 ft vertical required; synchronization required		

*Assuming no EIRP limit on UL (FCC rules) | *Will comply with ETSI spec to be released in July, 2010 (EN302 893 v1.5.1)



motorola.com/pmp

Printed in USA 11/09. MOTOROLA and the Stylized M Logo are registered in the US Patent & Trademark Office. All other product or service names are the property of their respective owners. ©Motorola, Inc. 2009. All rights reserved. For system, product or services availability and specific information within your country, please contact your local Motorola office or Business Partner. Specifications are subject to change without notice.